



SDS according to Regulation (EC) No. 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), Annex II-EU

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

Date issued 29.07.2014

### 1.1. Product identifier

Product name China Oil

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation Drying oil for treatment of outdoor wood furniture and floors.

### 1.3. Details of the supplier of the safety data sheet

Company name Arboritec AB  
 Postal address Olof Wijksväg 9  
 Postcode SE-444 65  
 City Jörlanda  
 Country Sverige  
 Tel 0303-563 30  
 Fax 0303-563 32  
 E-mail post@arboritec.com  
 Website http://www.arboritec.com  
 Contact person Jörgen Kaldemark

### 1.4. Emergency telephone number

Emergency telephone In case of medical emergency call:112

## SECTION 2: Hazards identification

### 2.1. Classification of substance or mixture

Classification according to 67/548/EEC or 1999/45/EC R65,R66  
 R48/20  
 Classification according to Regulation (EC) No 1272/2008 [CLP/GHS] H304;  
 H372;  
 EUH 066;

### 2.2. Label elements

#### Hazard Pictograms (CLP)



Composition on the label Hydrotreated heavy naphtha (petroleum):50 - 60 %  
 Signal word Danger  
 Hazard statements H304 May be fatal if swallowed and enters airways.  
 EUH 066 Repeated exposure may cause skin dryness or cracking.  
 Precautionary statements P102 Keep out of reach of children.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.  
 P405 Store locked up.  
 P501 Innehållet/behållaren lämnas till godkänd mottagare av farligt avfall.

### 2.3. Other hazards

Other hazards When spray applying see section 8.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Substance	Identification	Classification	Contents
Hydrotreated heavy naphtha (petroleum)	CAS no.: 64742-48-9 EC no.: 265-150-3	Xn R65,R66 R48/20 Asp. tox 1;H304; H372; STOT RE1; EUH 066;	50 - 60 %

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

General	Get medical advice/attention if you feel unwell. Never give anything by mouth to an unconscious person.
Inhalation	Use with adequate ventilation. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice. Get medical advice/attention.
Skin contact	Remove/Take off immediately all contaminated clothing. IF ON SKIN: Wash with plenty of soap and water. Do NOT use solvents or thinners. Wash skin thoroughly with soap and water.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if you feel unwell.
Ingestion	Do NOT induce vomiting. Risk of aspiration or chemical pneumonia. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media Recommended extinguishing media : alcohol resistant foam, CO2, powders, water spray. Do not use water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire and explosion hazards Fire will produce dense black smoke. Decomposition products can be hazardous. At high temperatures create: Carbon monoxide (CO), carbon dioxide (CO2), smoke, nitrogen gases (NOx).

### 5.3. Advice for firefighters

Personal protective equipment Wear respiratory protection.  
 Other Information Eliminate all ignition sources if safe to do so. Do not allow run-off from fire fighting to enter drains or water courses.

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures	See section 7 and 8.
Personal protection measures	In case of inadequate ventilation wear respiratory protection. Wear fire / flame resistant / retardant clothing. Use personal protective equipment as required. Wear cold insulating gloves / face shield / eye protection. Wear protective gloves / protective clothing / eye protection / face protection. Avoid breathing dust / fume / gas / mist / vapours / spray. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

## 6.2. Environmental precautions

Environmental precautionary measures	Collect spillage. Avoid release to the environment. If the product contaminates lakes, rivers or sewers, inform appropriate authorities in accordance with local regulations.
--------------------------------------	---

## 6.3. Methods and material for containment and cleaning up

Cleaning method	Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.
Containment	Keep away from sources of ignition Store in a well-ventilated place.

## 6.4. Reference to other sections

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Handling	Vapours may form explosive mixtures with air. Avoid spilling, skin- and eye contact. Avoid breathing dust / fume / gas / mist / vapours / spray. Avoid breathing dust.
----------	--

## Protective Safety Measures

Protective Safety Measures	Smoking, eating and drinking should be prohibited in application area. Remove contaminated clothing and protective gear before you get to an area where meals are taken.
Safety Measures To Prevent fire	Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.  In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only non-sparking tools.
Additional information	For personal protection see Section 8. Never use pressure to empty : container is not a pressure vessel.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage	Store in accordance with applicable regulations for good chemical practice. Keep only in original container. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight. Store in a dry place. Tillse att gällande arbetsmiljölagstiftning följs.
Conditions To Avoid	Keep away from heat / sparks / open flames / hot surfaces. — No smoking. Protect from sunlight. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Prevent unauthorized access.

## Conditions for safe storage

Storage Temperature	Value: 5-25 Celsius
---------------------	---------------------

## 7.3. Specific end use(s)

Recommendations Do not handle until all safety precautions have been read and understood.

## Specific end users

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure limit values

Substance	Identification	Value	TWA Year
Hydrotreated heavy naphtha (petroleum)	CAS no.: 64742-48-9	8-hour TWA: 300 mg/m <sup>3</sup>	
	EC no.: 265-150-3	15 min.: 15 mg/m <sup>3</sup>	

### 8.2. Exposure controls

#### Precautionary measures to prevent exposure

Appropriate engineering controls Use with adequate ventilation. If possible this should be achieved by local extraction and good exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory equipment.

#### Respiratory protection

Respiratory protection Respiratory protection with gas filter (brown A) must be used if air concentration exceeds acceptable level (OEL).

Mask type When spraying, use half-or full face mask with filter P2 (IIB) to spray.

#### Hand protection

Hand protection Wear cold insulating gloves / face shield / eye protection.

Skin-/ hand protection, long term contact For prolonged or repeated contact use gloves made of neoprene (1-4h) or nitrile (>4h).

Suitable materials Barrier creams may help to protect the skin, but they should however not be used once exposure has occurred.

#### Eye / face protection

Eye protection At the risk of splashing, close-fitting goggles or face shield.

Suitable Eye Protection Wear cold insulating gloves / face shield / eye protection.

#### Skin protection

Skin protection (except hands) Wear fire / flame resistant / retardant clothing.

#### Exposure controls

Safety measures for consumer use of the chemical Read label before use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Odour	As Solvent.
Comments, Odour limit	Not applicable.
Comments, pH (as supplied)	Not applicable.
Comments, pH (aqueous solution)	Not applicable.
Comments, Melting point / melting range	Not applicable
Comments, Boiling point / boiling range	Not applicable.
Flash point	Value: 64 °C
Comments, Evaporation rate	Not determined.
Flammability (solid, gas)	Not determined
Comments, Explosion limit	Not applicable.
Comments, Vapour pressure	Not determined.

Comments, Vapour density	Not determined.
Specific gravity	Value: 0,8-0,9 g/ml Method of testing: ASTM 6450 Test temperature: 20 °C
Solubility in water	Non-soluble.
Comments, Partition coefficient: n-octanol / water	Not applicable.
Viscosity	Value: > 20,5 mm <sup>2</sup> /s Test temperature: 40 °C
Explosive properties	Not determined.
Oxidising properties	Not applicable.

## 9.2. Other information

Content Of Voc	Value: < 700 g/l Comments: initial boiling point less than or equal to 250°C.
----------------	--

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	No reactive.
------------	--------------

### 10.2. Chemical stability

Stability	Stable under recommended storage and handling conditions (see section 7). Risk of self-ignition in porous materials such as insulation, rags and the like.
-----------	---

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	No dangerous if handled according to Technical Information.
------------------------------------	---

### 10.4. Conditions to avoid

Conditions to avoid	No applicable.
---------------------	----------------

### 10.5. Incompatible materials

Materials to avoid	Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reaction.
--------------------	---

### 10.6. Hazardous decomposition products

Hazardous decomposition products	When exposed to high temperature may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.
----------------------------------	---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicological data for substances

Substance	Hydrotreated heavy naphtha (petroleum)
LD50 oral	Value: > 2000 mg/kg Animal test species: Rat
LD50 dermal	Value: > 2000 mg/kg Animal test species: Rat
LC50 inhalation	Value: > 2800 mg/m <sup>3</sup> Animal test species: Rat

#### Potential acute effects

Inhalation	Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system.
Skin contact	Prolonged or repeated skin contact may cause irritation, dry skin, cracked skin and possibly eczema.
Eye contact	May cause irritation in eyes.
Ingestion	Ingestion may cause nausea and vomiting. Pneumonia may occur if the product by swallowing or vomiting is drawn into the respiratory tract.

Skin corrosion / irritation, other information	No information available.
Aspiration hazard, comments	When applying see section 8.
Eye damage or irritation other info	If splashed in the eyes, the liquid may cause irritation and reversible damage.

### Delayed effects / repeated exposure

General respiratory or skin sensitisation	Prolonged or repeated contact may defat the skin, resulting in non-allergic contact eczema and absorption through the skin.
STOT-single exposure	No information available.
STOT-repeated exposure	No information available.

### Carcinogenic, Mutagenic or Reprotoxic

Carcinogenicity human experience	No information is available.
Germ Cell Mutagenicity, human experience	No information available.
Reproductive toxicity	No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Toxicological data for substances

Substance	Hydrotreated heavy naphtha (petroleum)
Acute aquatic, fish	Value: > 100 mg/l Method of testing: LC50 Species: Oncorhynchus mykiss Duration: 96h
Acute aquatic, algae	Value: > 100 mg/l
Acute aquatic, Daphnia	Value: > 100 mg/l Method of testing: EC50 Species: Crustacea amphipods Duration: 96h
Bioconcentration factor (BCF)	Value: 112-159

### 12.2. Persistence and degradability

Persistence and degradability description	Not determined.
---	-----------------

### 12.3. Bioaccumulative potential

Bioaccumulative potential	Not determined.
---------------------------	-----------------

### 12.4. Mobility in soil

Mobility	Not determined.
----------	-----------------

### 12.5. Results of PBT and vPvB assessment

PBT assessment results	Not classified as PBT / vPvB of current EU criteria.
------------------------	--

### 12.6. Other adverse effects

Other adverse effects / Remarks	None known.
---------------------------------	-------------

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Specify the appropriate methods of disposal	Avoid release to the environment. Collect spillage. Wastes and empty containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.
Product classified as hazardous waste	Yes
EWC waste code	EWC: 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS, National

waste code: 01, National wastegroup: 11

## SECTION 14: Transport information

### 14.1. UN number

Comments Not dangerous goods.  
Transport in accordance with national law and ADR for road, RID for rail, IMDG for sea and ICAO / IATA for air. For complete information on transport, see transport document.

### 14.2. UN proper shipping name

ADR ---

RID ---

IMDG ---

ICAO/IATA ---

### 14.3. Transport hazard class(es)

### 14.4. Packing group

### 14.5. Environmental hazards

IMDG Marine pollutant Nej

### 14.6. Special precautions for user

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Legislation and regulations The labeling of the product according to EC directives 67/548/EEC, 1999/45/EC, see section 2.

Classification and labeling of substances according to Regulation (EC) 1272/2008 (CLP) is in section 2.

Classification and labeling of substances under Directive 67/548/EC, 1999/45/EC, see section 3.

Classification and labeling of substances according to Regulation (EC) 1272/2008 (CLP) is in section 3.

Safety data sheet is designed according to EU Commission Regulation No. 1907/2006.

### 15.2. Chemical safety assessment

Chemical safety assessment performed No

## SECTION 16: Other information

### Hazard symbol



R-phrases R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.

S-phrases S2 Keep out of the reach of children.  
S23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be

	<p>specified by the manufacturer).</p> <p>S51 Use only in well-ventilated areas.</p> <p>S56 Dispose of this material and its container to hazardous or special waste collection point.</p> <p>S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.</p>
Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]	; EUH 066; ; H304; ; H372;
List of relevant R-phrases (under headings 2 and 3).	R65 Harmful: may cause lung damage if swallowed. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. R66 Repeated exposure may cause skin dryness or cracking.
List of relevant H-phrases (Section 2 and 3).	EUH 066 Repeated exposure may cause skin dryness or cracking. H304 May be fatal if swallowed and enters airways. H372 Causes damage to organs through prolonged or repeated exposure
Version	1
Responsible for safety data sheet	Arboritec AB
Comments	The information of this SDS is based on the present state of our knowledge and on current EU and national laws. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product : it is not to be considered as a guarantee of the products' properties.